


SILICONE (600 MICRON)

TRUTAPE

Digital
Catalog




Dijital
Katalog



White

HT-606S




Black

HT-605S




Silver

HT-600S




Red

HT-601S




Blue

HT-602S




Yellow

HT-603S




Gray

HT-607S




Fluo Yellow

HT-610S



Fluo Orange

HT-613S



Fluo Red

HT-614S



Gold

HT-630S

REFLECTIVE SILICONE (250-280 MICRON)

Digital
Catalog



Dijital
Katalog



WDSR

White




WDSR

Black



WDSR

Silver



WDSR

Gold



Deseni Tersten Kesiniz
Cut The Image in Reverse



SILICONE (600 Micron)
165°C (329°F)
REFLECTIVE SILICONE
150°C -160°C (302°F-320°F)



4 Bar Basınç
4 Bar Pressure



SILICONE (600 Micron)
15 Saniye Presleme
15 Seconds For Pressing
REFLECTIVE SILICONE
10 Saniye Presleme
10 Seconds For Pressing



Soğuk Çekim
Cool Peel



SILICONE (600 Micron)
Lazer ve Plotter Kesim
Laser & Plotter Cutting
REFLECTIVE SILICONE
Lazer Kesim
Laser Cutting



Uygulamadan 24 Saat Sonra
After 24h Width Application



SILICONE (600 Micron)
Ebat/Size : 50cmx25m
Ağırlık / Weight : 9,5kg/roll
REFLECTIVE SILICONE
Ebat/Size : 50cmx25m
Ağırlık / Weight : 14,5kg/roll

UYARI Boyalı kumaşlarda migrasyon ihtimaline karşı üretim öncesi gerekli testlerin yapılmasını öneririz. Kullanılacak kumaşın içeriğine göre, basım talimatları değişebilir.

NOTICE We offer you to test the product against the color migration. Pressing instruction may change, according to the fabric type.